

CX 110

PROPERTY	TYPICAL VALUE	UNIT	FIA Specifications Appendix J – Art 252		TEST METHOD
			Min.	Max.	
Aspect	clear/limpid	-	To report		Visual
Colour	White	-	To report		Visual
RON	109	-	95	102	EN-ISO 5164
MON	99	-	85	90	EN-ISO 5163
Density at 15° C	758	kg/m ³	720	785	EN-ISO 3675
Oxygen Content	2,70	%wt	-	3,7	Elemental analysis
Nitrogen Content	<0,1	%wt	-	0,5	ASTM D 3228
Peroxides and nitroxides Content	<10	ppm	-	100	ASTM D 3703
Lead Content	<0,003	g/l	-	0,40	ASTM D 3237
Benzene Content	<0,5	%vol	-	5	ASTM D 3606
Reid vapour pressure	472	hPa	-	900	ASTM D 323
Sulphur content	<0,005	%wt	To report		EN ISO 20884
Aromatic content	<35	%vol	-	35	ASTM D 1319
Distillation:					ISO 3405
Evaporated at 70 °C	25	%vol	10	47	
Evaporated at 100 °C	56	%vol	30	70	
Evaporated at 180 °C	97	%vol	85	-	
Final Boiling Point	147	°C	-	225	
Residue	0,6	%vol	-	2	

*This fuel contains MTBE.

*This fuel does not comply with the Australian Fuel Quality Standard Act.